PUSR®
www.pusr.com

Communication Expert
of Industrial IOT

Industrial Protocol Converter

USR-PX530



Introduction

The USR-PX series are the latest industrial protocol converters for automation applications lunched by PUSR. With simple parameter configuration, these devices enable efficient conversion between major industrial protocols including EtherCAT, PROFINET, CANopen, and Modbus and will continue to expand, bridging industrial communication between different protocols.

The USR-PX530 model in this series is a PROFINET to Modbus industrial field bus protocol converter. On the network side, it acts as a PROFINET Slave device, featuring 2 PROFINET ports, 1 RS485 interface, and 1 standard 10/100M Ethernet interface. It easily integrates Modbus slave devices from the industrial field into PROFINET master devices.

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000

Product Features

Reliability & Stability

- Aluminum casing with IP40 protection
- Industrial-grade design for extreme temperatures (-20°C to +70°C)
- Wide-voltage input (DC 9-36V) with reverse polarity protection
- EMC Level 3 protection, with full isolation for all the interface
- DIN-rail 35mm mounting

Rich Interface

- Dual PROFINET ports (IN/OUT) with integrated switch, redundant link
- 1 standard Ethernet port for parameter configuration
- 1 Type-C interface for debugging
- 1 optically isolated RS485 serial port

Powerful Functionality

- Compliant with PROFONET standards for seamless integration with mainstream PROFINET masters (e.g., PLCs)
- Supports PROFINET slave to Modbus RTU/TCP master conversion
- Supports up to 1400 input/output bytes, with support for 16 slots
- Modbus RTU supports 32 slaves; Modbus TCP supports up to 8 slaves
- Edge data collection and computation for up to 2,000 data points
- Provides GSDML file for import into PROFINET master devices.
- Configuration via PC software, with CSV file import/export
- One-click factory reset (hardware/software)
- Built-in 120Ω terminal resistor, configurable via software
- Modbus function codes: 01, 02, 03, 04, 05, 06, 15, and 16
- User-defined IP address, port, slave ID, and register settings

Dimensions

Unit: mm





Figure 1 **Dimension of USR-PX530**

Application



Specifications

Catalog	Parameters	Value
Power Supply	Power Input	9-36V DC, 12V/1A is recommended
	Working Current	Idle: 158mA/12V (avg), 163mA/12V (max); Full load: 162mA/12V (avg), 165mA/12V (max)
	Connector	5.08×2P pluggable terminal block with anti-reverse and screw lock
RS485 Interface	Connector	3.81×3P pluggable terminal block with screw lock
	Pin	A (RS485 A), B (RS485 B), G (GND)
	Baud Rate	600~230.4K bps
	Data bits	8
	Stop bit	1, 2
	Parity bit	None, Odd, Even
Ethernet Port	PROFINET	2× PROFINET (P1, P2), 10/100Mbps auto-negotiation, integrated switch function
	Ethernet	1× RJ45 port (10/100Mbps, auto MDI/MDIX), for parameters configuration
	Default IP	192.168.0.7
	Gateway IP	192.168.0.1
Other Interface	Indicators	PWR, WORK, 485, PN
	Reload Button	Press for 3-15s to restore factory settings
	Type-C	Debugging interface for troubleshooting
Physical Parameters	EMC Protection	IEC 61000-4-2(ESD): 6kV contact, 8kV air IEC 61000-4-5(Surge): 2kV common mode, 1kV differential mode for power; 2kV for Ethernet/RS485 IEC 61000-4-4(EFT): 2kV for power, 1kV for Ethernet/RS485
	Isolation	Isolation for both serial, Ethernet, CAN, and power
	Dimension	120×85×30mm (without terminals/rail); 137.3×30×109.3mm (with terminals/rail)
	Installation	DIN rail mounting, aluminum housing
	Operating Temperature	-20℃ to +70℃
	Storage Temperature	-40℃ to +105℃ (non-condensing)
	Operating Humidity	5%-95% (non-condensing)
Software	Protocol	PROFINET slave to Modbus RTU/TCP master
	PROFINET protocol	Supports 16 slots, up to 1400 input/output bytes
	Modbus protocol	Edge data collection and computation for up to 2000 data points
	Setup	PX Tool

Ordering Guide

Model	Protocol	Interface

USR-PX520	EtherCAT slave to Modbus RTU/TCP master	2 * EtherCAT, 1 * RJ45, 1 * RS485
USR-PX530	Profinet slave to Modbus RTU/TCP master	2 * Profinet, 1 * RJ45, 1 * RS485
USR-PX511	CANopen slave to Modbus RTU/TCP master	1 * CAN(FD), 1 * RJ45, 1 * RS485
USR-PX521*	EtherCAT slave to Modbus RTU/TCP master EtherCAT slave to CANopen master	2 * EtherCAT, 1 * RJ45, 1 * RS485, 1 * CAN(FD)
USR-PX531*	Profinet slave to Modbus RTU/TCP master Profinet slave to CANopen master	2 * Profinet, 1 * RJ45, 1 * RS485, 1 * CAN(FD)

*: *In processing*

Purchase & Support

For more information, please visit our websites:

- Official website: **https://pusr.com**
- Official shop: **https://shop.usriot.com**
- Technical support: **http://h.usriot.com/**

Your Trustworthy Smart IOT Partner

PUSR®
www.pusr.com

Official Website: www.pusr.com

Official Shop: shop.usriot.com

Technical Support: h.usriot.com

Inquiry Email: inquiry@usriot.com

Skype & WhatsApp: +86 13405313834

Click to view more: Product Catalog & Facebook & Youtube

LRI Distribuída no Brasil pela LRI | vendas@lri.com.br | 51 2129-3000